

IONIX INSTRUMENTS

VALUE LINE

TESTER SERIES 1

pH, Conductivity, TDS and Salinity

Battery Life Indicator

Large STN display with 180° viewing angle and simultaneous temperature display

Measurement stability icon

Calibration Indication

Multi calibration with auto recognition of standards

Easy to grip body design



Long lasting electrode with polymer reference electrolyte



Premium carry case complete with standards



Extended working hours with 4 x AAA batteries (compatible with rechargeable batteries)



Durable and waterproof to IP67 standards



Floats on water



Lanyard and clip for convenience



Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384






Email: info@rainbowpoolproducts.com.au

Web: www.rainbowpoolproducts.com.au

Ionix Waterproof pH1 Tester Kit

Code: PH1C

Value Pocket Testers specifications

					
Model		pH1	EC1	TDS1	Salt1
Measure		pH / °C	Conductivity / °C	TDS / °C	Salinity / °C
Parameter	Range	0~14.0 pH 0~50.0°C	0~200.0 µS/cm 0~2000 µS/cm 0~20.00 mS/cm 0~50.0°C	0~100.0 ppm 0~1000 ppm 0~10.00 ppt 0~50.0°C	0~10.00 ppt 0~50.0°C
	Resolution	0.1 pH; 0.1°C	0.1/1 µS; 0.01 mS; 0.1°C	0.1/1 ppm; 0.01 ppt; 0.1°C	0.01 ppt; 0.1°C
	Accuracy	±0.1 pH; ±0.2°C	±1% F.S; ±0.2°C	±1% F.S; ±0.2°C	±1% F.S; ±0.2°C
	ATC	0~50.0°C	0~50.0°C	0~50.0°C	0~50.0°C
	Calibration	1~3 pts	1~2 pts	1~2 pts	1 pt
Function	Auto Stable	“☺” displays when measurement is stable			
	Self-diagnosis	Yes	Yes	Yes	Yes
	Low Battery Indicator	Battery icon: 			
	Power	DC 3V, AAA batteries x 4			
	Operation Life	Continuous operation > 400 hrs	Continuous operation > 200 hrs	Continuous operation > 200 hrs	Continuous operation > 200 hrs
	Auto. Power off	Auto power off after 8 minutes of inactivity			
	LCD	Type: STN , 180° viewing angle			
	IP Rating	IP67 water-proof and dust-proof; floats on water			
Weight and Dimensions	Tester: 40x31x178 mm/107 g ; Carry case: 190x165x40 mm/438 g				
Warranty	Tester: 12 months				

User Customization

	pH1	EC1	TDS1	Salt1
	pH Buffer Standard (US - NIST)	Range (Auto - µS - mS)	TDS Factor (0.40~1.00)	Salinity Unit (ppt - g/l)

Complete Kit

pH1	pH1 tester / 1x50ml pH7.00 and pH4.00 Buffer Solution / 4xAAA Batteries / Lanyard / Carry Case
EC1	EC1 tester / 1x50ml 1413 µS and 12.88 mS Calibration Solution / 4xAAA Batteries / Lanyard / Carry Case
TDS1	TDS1 tester / 1x50ml 1413 µS and 12.88 mS Calibration Solution / 4xAAA Batteries / Lanyard / Carry Case
Salt1	Salt1 meter / 4xAAA Batteries / Lanyard / Carry Case



Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au

Web: www.rainbowpoolproducts.com.au