



IX Series Leaf Canister

INSTALLATION AND OPERATING INSTRUCTIONS



Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au

Web: www.rainbowpoolproducts.com.au

INSTALLATION

1. Install Leaf Canister filter on a clean, stable and level base. Canister should be installed on the inlet side of the pump.
2. The leaf canister has one inlet ports (from Pool/Spa) and three outlet ports (to Pump). Glue 50mm tail into the inlets and one 50mm tail into one of the outlets of the filter that suits the plumbing configuration.
3. Glue in blanking caps into the two remaining inlets. Allow a minimum on one hour for glue to dry.

START UP INSTRUCTIONS

1. Before start up make sure the canister basket is in the tank.
2. Fill canister with water to top.
3. Fit lid and lock ring and ensure it is in place and tightened.
4. Close both the Air Bleed Screws fitted to the lid.
5. Start pump – Check there is a good flow of water back in the pool.
6. Clean the basket when the flow to the pool reduces.

TO CLEAN CANISTER BASKET

1. Stop pump-close valves on the suction and return lines of the canister.
2. Open one the air bleed valve on the lid.
3. Loosen lock ring and remove basket.
4. Lift out basket. Remove debris with hand. Do not bang against hard surfaces to remove debris; Damage to basket may occur voiding warranty. Replace the basket – carefully locating it on the bottom spigot.
5. Clean the lid 'o' ring. Replace the lid and press firmly into place.
6. Tighten the lid lock ring until safety catch locks.
7. Fill with water
8. Close the valves – start the pump.

**NEVER LOOSEN THE LOCK RING WHEN
THE PUMP IS WORKING**

WARRANTY

Your IX Leaf Canister is covered by a limited five year warranty against defects in materials or manufacture. The outer case, lid and lock ring are covered for a period of five years from date of purchase plus 30 days to allow for installation.

The basket is a consumable item and is covered for a period of 30 days. Regular cleaning will ensure a longer life.

In field labour warranty applies only within capital city metropolitan areas or within 20 kilometers of an authorised Hurlcon service agent. Should you reside outside these locations, a traveling charge may be applied. Should the gauge or cartridge element fail, it must be returned to Hurlcon freight pre paid for repair or replacement at our option.

Hurlcon shall not be responsible for consequential damages of any kind. This warranty does not cover damage caused by accident or misuse. The warranty is only valid when the filter is used on swimming pool and spa pool applications only. No person is authorised to make representations on behalf of Hurlcon.

Commercial Installations

On Commercial Installations, such as health clubs, motels/hotels and hydrotherapy, parts and in field labour warranty (within capital city metropolitan areas or 20km radius of authorised service agents) is 12 months from the date of purchase plus 30 days. The cartridge element is warranted for 30 days.