



## Salt Water Electrolysers/Chlorine Generators; AC Series

- Non-reverse Polarity
- Powered By Transformer Power Supply
- Salinity Range: 4,500 – 6,500 mg/L

Model	Chlorine Gas Equivalent	Input AC Power Consumption	Water Flow	Dimension (Packaged)	Weight Gross
	Grams/Hour	kW	Litres/minute	L x W x H (cm)	Kg
ACMINI	5	0.070	200 – 400	37 x 31 x 22	11
AC15	15	0.215	200 – 400	37 x 31 x 22	11
AC20	20	0.290	200 – 400	37 x 31 x 22	11
AC25	25	0.360	200 – 400	37 x 31 x 22	11
AC35	35	0.505	200 – 400	43 x 33 x 27	14
AC50	50	0.540	200 – 400	43 x 33 x 27	16
AC50HD	50 With Heavy Duty Grade Electrodes	0.720	200 – 400	43 x 33 x 27	16
AC100HD	100 With Heavy Duty Grade Electrodes	1.440	200 – 400	47 x 44 x 28	28

### Options (Available to Australian customers only)

Prefix	Description	Additions available for
T	Timer Option	Mini/15/20/25/35/50/50HD
QT	Timer With Battery Back Up	Mini/15/20/25/35/50/50HD
L12	Underwater Light Option 12V	Mini/15/20/25
L24	Underwater Light Option 24V	Mini/15/20/25
L32	Underwater Light Option 32V	Mini/15/20/25
S	Seawater Configuration	All Models

NB: When ordering desirable model with options, simply add prefix to the model code. Example: AC25 TL12