



## DAVEY

### APPLICATIONS

Ideal for most swimming pool applications such as:

- Filtration
- Auto pool cleaning
- Backwashing
- Water features
- Spa jet operation
- Solar pool heating

### WHY CHOOSE THE Silensor® Series 50Hz pump?

**Super-Quiet** - Designed with a unique water-cooled motor which captures noise and vibrations, allowing super-quiet operation rated at 55 dBA. Your neighbours won't even know it's there.

**Long Lasting** - Silensor is designed for long service life in an outdoor, poolside environment and replaces highly corrodible metal components with high performance, long-life plastics for low maintenance and dependable service – year after year.

**Dependable** - Silensor incorporates unique dry run protection to minimise pump damage if no water is available to the pump. It also includes a unique mechanical seal protection for long service life and reduced maintenance.

**Convenient** - By water-cooling the motor, Silensor does not require air ventilation, and gives installers more flexibility with pump positioning.

- SLS models are an ideal replacement for many other pool pump models and are designed to retrofit with minimal hassle.
- SLL models feature a large leaf basket for long intervals between cleaning.



SLS




SLL

DAVEY  
**SILENSOR**  
SERIES


### 50Hz Super Quiet Pool Pump

Davey's water-silenced pool pumps offer super-quiet operation with high efficiency, making them the ideal choice for modern swimming pools.







ELECTRICAL DATA								
Model	SLS100	SLS150	SLS200	SLS300	SLL150	SLL200	SLL300	SLL400
Voltage (V)	220 / 250							
Supply Frequency (Hz)	50							
Motor Input Power (W/HP)	740/1.0	860/1.2	1090/1.5	1400/1.9	870/1.2	1130/1.5	1400/1.9	1760/2.4
Motor Output Power	525/0.7	620/0.8	775/1.0	960/1.3	635/0.8	830/1.1	960/1.3	1200/1.6
RPM	2850							
Enclosure Class (IP)	56							
Insulation Class	F							
Approval No.	V06258							
Lead Length	3m							



OPERATING LIMITS	
Max. water temperature	40°C / 104°F
Max. ambient temperature	40°C / 104°F
Noise level (AS 5102.2)	55dBa

DIMENSIONS (mm)				
Model	Mounting Holes Diameter	Inlet PVC	Outlet PVC	Net Weight (kg / lbs)
SLS 100	10 x 34 deep	40 / 40	40 / 40	11.0
SLS 150		40 / 40	40 / 40	11.0
SLS 200		40 / 40	40 / 40	11.5
SLS 300		40 / 40	40 / 40	11.5
SLL 150		40 / 50	40 / 50*	11.5
SLL 200		40 / 50	40 / 50*	12.5
SLL 300		50	50	12.5
SLL 400		50	50	13.0



\* Suction & delivery accept 40mm PVC pipe on the I.D. and 50mm fitting on the O.D.



**Rainbow Pool Products**

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: [info@rainbowpoolproducts.com.au](mailto:info@rainbowpoolproducts.com.au)

Web: [www.rainbowpoolproducts.com.au](http://www.rainbowpoolproducts.com.au)