

# Pressure Tanks

## Onga Aquapack Steel pressure tanks

Each pressure tank in the Onga range is constructed to store supply water under pressure to provide a buffer for your plumbing or piping, to minimise pump operation time and to maximise pump life. Onga has a wide range of pressure tanks to suit any needs. From the small Aquapack AP10 to the largest Sta-Rite Signature 2000, Onga offers a range from 3L to more than 450L.

### Aquapack Range



The Onga Aquapack range starts with the moulded 3 litre AP10 and continues up to the AP80. The range includes specialist models like the corrosion-resistant AP50S in stainless steel, and the AP80HP for high pressure applications. There's a model to suit every application. Riva-flo 130 included in Aquapack range.

### AP80HP



Onga also caters for high pressure applications such as multi-storey water supply or high pressure, deep well sites with the Aquapack AP80HP tank, rated to 1520kPa.

### AP50S



The Stainless steel Aquapack AP50S provides a 24L tank constructed from 304 grade stainless steel. This gives it incredible corrosion resistance\*.  
\* Not recommended for water with very high chloride levels.  
In this case we recommend using a signature 2000 tank.

### Pro-Source Range



The Pro-Source range offers large steel tanks for high volume applications – they make great partners for the 70–150 Lpm submersible pumps



#### Aquapack steel pressure tanks features

Replaceable bladders available	Extends the useful life of the product
Stainless steel inlet flange/connection	Corrosion resistance and strength at connection point
Wide range available	Optimise your pressure system

Pressure Switch Settings kPa	THEORETICAL DRAW OFF IN LITRES								
	AQUA PACK MODELS							PRO-SOURCE	
	10	18	50	50s	80	80HP	RF130	PS42T	PS80T
100 - 200	1.1	2.8	8	8	11.3	11.3	20.1	24.4	44.2
140 - 275	1.2	3	8.8	8.8	12.3	12.3	21.9	26.6	48.2
210 - 340	1	2.5	7	7.4	10.4	10.4	18.5	22.5	40.7
275 - 415	0.9	2.2	7.4	6.4	9	9	16	19.5	35.3
275 - 450		2.6	7.5	7.5	10.5	10.5	18.8	22.8	41.3
345 - 550		2.6			10.6	10.6	18	23	41.8
410 - 620		2.4			9.6	9.6	17.2	20.8	
480 - 690		2.2			8.8	8.8	15.7	19	
760 - 1000					8.2	8.2			
960 - 1240						6.9			
1100 - 1380						6.3			
<b>Vol litres</b>	3.2	8.2	24	24	34	34	60	72	133
<b>Max Rating kPa</b>	<b>380</b>	<b>690</b>	<b>435</b>	<b>550</b>	<b>1000</b>	<b>1520</b>	<b>790</b>	<b>690</b>	<b>570</b>
<b>Dia (cm)</b>	21	20	33	32	36	36	38	40	50
<b>Height (cm)</b>	24	33	38	37	40	40	85	78	87
<b>Inlet size (BSP)</b>	3/4"F	1"M	1"M	1"M	1"F	1"F	1"F	1"F	1"F
<b>Weight (kg)</b>	1.6	2.4	5.7	3.6	10.7	10.7	16	26	33
<b>Warranty (yrs)</b>	1	1	1	5	1	1	1	4	4



## Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au

Web: www.rainbowpoolproducts.com.au

