



High Performance Heater

Ultra-high Performance in a compact quiet and ECO-friendly design.







The Turbotemp heater's easy-to-read controls make system operation and monitoring simple. Pool and spa temperatures can be pre-set and controlled with the push of a button. A digital display indicates the water temperature, and five LED lights give you system status and let you know if the heater needs service.

POOL SIZING*

		Heater Size		Heater Size			
°C Temperature Change/	Model 200	Model 300	Model 400	Model 200	Model 300	Model 400	
24 Hrs.	Ро	ol Capacity Litres	y in	Pool Surface Area in Sq. Mt. at 1.65m Depth			
2.77	368,635	552,954	737,269	220	329	439	
5.44	184,315	276,475	368,635	110	165	220	
8.31	122,878	184,319	245,756	73	110	146	
11.08	92,160	138,239	184,315	55	82	110	
13.85	73,728	110,595	147,453	44	66	88	
16.62	61,437	92,156	122,878	37	55	73	
19.39	52,663	78,994	105,325	31	47	63	
22.16	46,080	69,122	92,160	27	41	55	



High Performance Gas Pool Heaters

FAST, EFFICIENT, COMPACT, QUIET SAFE AND ECO-FRIENDLY

No matter what you're seeking in your swimming pool heater, the Turbotemp heater measures up. Compare this list of features to any other and you'll see why Turbotemp heaters are setting a new standard for total value.

- Very compact design.
- A fully pre-mixed burner system with a highly efficient air and gas mixture.
- Hot surface ignition eliminating the requirement for a pilot.
- Push button digital controls with easy to view rotating display.
- Engineered for super quiet operation.
- · Certified for low NOx emissions.
- · Safe operation through a series of features including:-
 - ☐ Water pressure switch
 - Over temperature switch
 - ☐ Stack flue sensor
 - ☐ Manual gas shut-off for servicing
- Approved for installation on combustible surfaces.





SPA SIZING*

	Spa Volume (Litres)										
Model	750	1,150	1,500	1,900	2,250	2,650	3,000	3,400	3,800		
	Minutes for 16.2°C (30°F) Temperature Rise (Heater Input in 1000 BTU/HR)										
200	18.0	27.0	35.0	44.0	53.0	62.0	71.0	80.0	89.0		
300	13.5	20.0	26.5	33.0	40.0	46.5	53.0	60.0	66.5		
400	9.0	13.0	18.0	22.0	27.0	31.0	35.0	40.0	44.0		